

Outdoor Unit Model		TM18H4O	TM24H4O	TM30H4O	TM36H4O	TM42H3O
Number of Zones		2	2~3	2~4	2~5	2~5
Compressor Type		DC Inverter-Driven Rotary				
Energy Star		Yes	Yes	Yes	Yes	No
Coil Type		Copper Aluminum with Anti-Corrosion Coating				
PERFORMANCE NON-DUCTED INDOOR UNIT						
Cooling Capacity (min-max)	Btu/h	18,000(7,000~21,000)	24,000(7,500~33,000)	28,500(8,200~33,400)	34,000(8,900~35,800)	39,000(8,900~40,900)
SEER/EER *		22/12.5	21/12.5	21/12.5	21/12.5	21/10.4
Heating Capacity (min-max)	Btu/h	19,000(8,500~22,600)	24,000(7,500~35,000)	30,000(8,200~32,400)	42,500(8,900~44,400)	45,000(8,900~46,100)
HSPF/COP		11.0/3.7	11.0/3.7	11.0/3.7	11.0/3.7	10.2/3.6
PERFORMANCE- SLIM DUCTED INDOOR UNIT						
Cooling Capacity (min-max)	Btu/h	18,000(7,000~21,000)	24,000(7,500~33,000)	28,400(8,200~33,400)	34,000(8,900~35,800)	39,500(8,900~40,900)
SEER/EER *		16/11.5	16/11.5	16/10.5	16/11.5	15/9.8
Heating Capacity (min-max)	Btu/h	19,000(8,500~22,600)	26,000(7,500~35,000)	30,000(8,200~32,400)	42,500(8,900~44,400)	45,000(8,900~46,100)
HSPF/COP		11.0/3.7	11.0/3.7	11.0/3.7	11.0/3.7	10.2/3.6
OUTDOOR UNIT						
Cooling Temperature Range	F	0~118	0~118	0~118	0~118	0~118
Heating Temperature Range	F	-4~75	-4~75	-4~86	-4~86	-4~86
Sound Level	dB(A)	56	59	59	61	61
INSTALLATION						
Pre-Charge Length	ft	33	98	131	131	131
Total Line Length	ft	66	197	230	246	246
Length to farthest Indoor Unit	ft	33	65	82	82	82
Elevation (ODU above IDU)	ft	32	32	49	49	49
Line Connection Size - Liquid ~ Gas/Suction	Port A	1/4~3/8	1/4~3/8	1/4~3/8	1/4~3/8	1/4~3/8
	Port B	1/4~3/8	1/4~3/8	1/4~3/8	1/4~3/8	1/4~3/8
	Port C		1/4~3/8	1/4~3/8	1/4~3/8	1/4~3/8
	Port D			1/4~3/8	1/4~3/8	1/4~3/8
	Port E				1/4~3/8	1/4~3/8
ELECTRICAL						
Voltage/Phase/Hertz		208-230V/1/60Hz	208-230V/1/60Hz	208-230V/1/60Hz	208-230V/1/60Hz	208-230V/1/60Hz
MCA	amp	16	23	20	23	24
MOCP	amp	25	30	30	35	40
DIMENSIONS						
Unit dimension (WxDxH)	in	38.0x15.6x27.6	38.6x17.3x31.1	38.6x17.3x31.1	45.5x18.9x43.9	45.5x18.9x43.9
Package Dimension (LxWxH)	in	40.4x17.9x28.9	42.5x18.9x33.1	42.5x18.9x33.1	43.9x19.1x45.5	43.9x19.1x45.5
Outdoor Unit Weight (Net/Gross)	lbs	114.4/124.3	152.9/163.9	154.0/169.4	198.0/215.6	198.0/216.0
Limited Warranty		7 Years on Compressor and 5 Years on Parts				